

CLEAR

NEW

FRAMELESS DOORS PROFILE



SLIDING
DOORS



- Maximum visibility.
- Easy installation

CUTTING-EDGE AND ELEGANT DESIGN FOR ENTRYWAYS

The CLEAR2 model offers a highly attractive architectural glass appearance. It is designed for doors where, for aesthetic reasons, visible profiles must be avoided and exposed glass is the best option.

This model is ideal for interior entrances and especially suited for office environments.

The CLEAR2 profile is installed at the top, and thanks to the anti-slip material inside the clamp, it holds the glass securely in place by pressure, ensuring a firm grip for panels weighing up to 150 kg.

The CLEAR2-10 model is suitable for 10 mm thick glass

The CLEAR2-12 model is designed for 12 mm thick glass

It is available in two lengths: 1000 mm and 1500 mm.

It comes with a plastic cap that softens the contact between panels, leaving a small gap to prevent glass-to-glass collision.



CLEAR

FRAMELESS DOORS PROFILE

TECHNICAL FEATURES

	CLEAR 2-10		CLEAR 2-12	
	1000	1500	1000	1500
Type of clamp	Long clamp (1 unit per leaf)			
Dimensions	1000 x 65x21	1500 x 65x21	1000 x 65x23	1000 x 65x23
Glass thickness	10mm		12mm	
Max. weight / leaf	150 kg			
Max. width / height	1000/ 3000		1500/ 3000	
Material	Aluminium 6063			
Standard colour	Anodised silver			
Fastening	Clamping screw pressure			


The new range of operators is compatible with Erreka profiles and is available in customised finishes.

	RUN10			RUN15		
	RUN10	RUN10P	RUN10T	RUN15	RUN15P	RUN15T
CLEAR	✓	✓	✗	✓	✓	✗

ACCESSORIES

TYPES OF FLOOR GUIDES

GUIA01 Outer floor guide



INSTALLATION LAYOUT

