COMPACT



PROFILE

Framed Doors





Designed to offer the highest performance in sealing and robustness, taking care of aesthetics.

COMPACT model is designed for high performance in terms of robustness, paying attention to the aesthetics.

Installation uses a SNAP-IN SYSTEM with extremely simple profiles, allowing us to first install the Operator and frames and insert the glass with the framed profiles afterwards, making assembly and delivery times quicker.

The assembly of the framed profiles is carried out by means of mitred, bolted joints.

To seal the moving leaves, it has a frame with rounded edges and a brush seal, making it more airtight and secure.

As the door opens, the seal has a rounded overlap which reduces the likelihood of damage due to catching.

The closing and overlapping profiles are 8 mm wide profiles that ensure greater airtightness when the door is closed. The design is rounded to avoid damage in the event of impact and/or trapping between the door leaves.

The glazing joints are made with an EPDM coextrusion profile.

The COMPACT profiles offer enough flexibility to create mullioned door leaves, top windows or different configurations according to installation needs.

SNAP-IN PROFILES SYSTEM FOR EASY INSTALLATION AND CHANGE OF GLASS

SUITABLE FOR THE OPERATORS ERTAIN, GLOBAL AND TELESCOPIC





COMPACT SLIM

COMPACT SENDO

CONNECTED ACCESS

COMPACT

PROFILE

TECHNICAL FEATURES

	COMPACT SLIM	COMPACT SENDO
Dimensions: Depth (D) x Height (H)	Horizontal profile 45X45 mm	Horizontal profile 45x68 mm
	Vertical profile 45x45 mm	Vertical profile 45x68 mm
Material	aluminium	
Standard colour	silver*	
Max. door leaf size	2800 mm / 160 kg	3000 mm / 180 kg
Leaf width	Min. 500 mm - Max.1600 mm	Min. 500 mm - Max.2000 mm
Glass fastening	snap-in profile	
Fastening to carrier	adjustable carrier bracket	
Glass thickness	6 mm - 26 mm**	
Mechanical manual lock	not available	Optional ZSEG6

ACCESSORIES



INSTALLATION LAYOUT







CONNECTED ACCESS

www.erreka.com