

HIPPO



ELECTROMECHANICAL MOTOR

Sliding Gates

230 Vac / 400 Vac motor for sliding gates
up to 4000 kg.

Oil bath gear.



CONDOMINIUM




INDUSTRIAL

INTENSIVE USE

THREE-PHASE MOTOR

MECHANICAL LIMIT SWITCHES



Practical unlocking
system

HIPPO

ELECTROMECHANICAL MOTOR

TECHNICAL CHARACTERISTICS

	HP4000C
Power supply (Vac/Hz)	-
Power consumed (W)	750
Absorbed current (A)	2,5
Capacitor (µF)	-
Motor voltage (Vac)	3X400/50-60 3X230/50-60
Torque (Nm)	180
Speed (m/min)	8
Lock	Yes
Limit switches	Yes
Encoder	No
Pinion	M4-Z20
Duty cycle	S3-70%
Protection level	IP54
Operating temperature (°C)	-25/+70
Motor weight (kg)	40
Packaging dimensions (cm)	40x37x83
Maximum weight of the leaf (kg)	4000

RECOMMENDED KITS

		MOTOR	CONTROL PANEL	RECEIVER	REMOTE CONTROL	PHOTOCELL	FLASHING LAMP
		HP4000C	VIVO-T101	IRRE2-250	IR02	FT06	LUMI
HIPPO2	3x230 Vac	•	•	•	••	•	
HIPPO3	3x400 Vac	•	•	•	••	•	•

INSTALLATION LAYOUT

