CE2150 FC FCC ID: UXS-IPM165F C: 6902A-IPM165US Microwave Touchless

Wicrowave Touchless Switch (ClearWave) Instruction Manual



Toggle or Pulse

The ClearWave is a highly sensitive, high performance switch designed to activate automatic doors by detecting the movement of a person or object. For the safe and accurate use of this product, please read this instruction manual carefully.

1 Technical specifications

 Technology :
 Microwave Motion Sensor

 Microwave Module :
 24.125GHz

 Product Size :
 85.9mm × 85.9mm × 20mm (W × L × H)

 Detection Range [Hand] :
 ±5~40cm

 Detection Mode :
 Motion (Bi-directional)

 Speed of Target :
 Min. ±3cm/s, Max. ±1.5m/s

Power Supply: DC 12~30V, AC 12~24V Current Consumption: < 1.4W Output: Relay Contact (1A/24VDC) Output Hold Time: 1.2Sec. (PULSE mode) Operating Temp/Humidity: -20°C~+60°C/0~90% International Protection: IP54

2 General Information



3 Installation Guide

Cable Hole



Caution

Do not supply power during installation.

Do not disassemble or modify the device, it may cause fire or electric shock

4 Sensitivity Adjustment



5 Toggle mode / Pulse mode



6 Mounting Information



Hotron Ltd. 26 Dublin Street, Carlow, Ireland Tel: +353 (0)59 914 0345 Fax: +353 (0)59 914 0543 www.hotron.com